END-TO-END












SCOOTERS	Revo® 2.0 [14]	PX4 [13]	Pursuit 2 [13]	Pursuit XL[13]	Victory® LX [13]	Colt Sport [13]	Pursuit ES [13]	Victory® 10.2 [14]	Victory® Twin [13]	Maxima [13]
MODEL NUMBER	S67	SC134	SC7132	SC714	S710LX	S710DXW	SC713CA SC713HS	S6102 (3-Wheel) S7102 (4-Wheel)	SC712	SC901 (3-Wheel) SC941 (4-Wheel)
WEIGHT CAPACITY	400 lb / 181 kg	500 lb / 227 kg	350 lb / 158.7 kg	400 lb / 181 kg	400 lb / 181 kg	350 lb / 158.7 kg	350 lb / 158.7 kg	400 lb / 181 kg	350 lb / 158.7 kg	500 lb / 227 kg
SPEED (MAXIMUM) [2]	5.2 mph 8.4 km/h	9.2 mph / 14.8 km/h	9.3 mph / 15 km/h	7.5 mph / 12 km/h	5.6 mph / 9 km/h	7.43 mph / 11.96 km/h	CA: 6 mph / 9.7 km/h HS: 9.5 mph / 15.3 km/h	5.2 mph / 8.4 km/h	5.7 mph / 9.2 km/h	5.8 mph / 9.3 km/h
GROUND CLEARANCE [4]	1.25" at transaxle 3.5" at mid-frame	3.5" at motor 4.4" at mid-frame	3.8" at transaxle	5.25" at rear frame	2.3" at motor 2.8" at front frame	2.13" at motor	3.5" at motor	2.5" at motor	2.25" at motor	SC901: 2.5" at motor 3" at mid-frame SC941: 2.25" at motor
3-WHEEL TURNING RADIUS [4]	N/A	N/A	N/A	N/A	N/A	N/A	N/A	42"	42"	49"
4-WHEEL TURNING RADIUS [4]	52"	82.3"	69.3"	82"	61.25"	51.7"	68.5"	45.5"	N/A	53"
3-WHEEL LENGTH/ WIDTH [4,10]	N/A	N/A	N/A	N/A	N/A	N/A	N/A	45" / 22.25"	46" / 22.3"	47.5" / 27"
4-WHEEL LENGTH/ WIDTH [4,10]	47" / 20.75"	56" / 27.8"	53.5" / 25.60"	56.25" / 27.25"	47" / 22.5"	47" / 25.94"	53.5" / 25"	47.25" / 22.25"	N/A	47.5" / 27"
FRONT TIRES [4]	9" solid or pneumatic	13" pneumatic	13" pneumatic	13" pneumatic	10" solid or pneumatic	10" pneumatic (flat-free optional) [7]	13" pneumatic (flat-free optional) [7]	10" solid (pneumatic optional) [7]	(2) 9" solid	SC901: 10.5" solid SC941: 10" solid
REAR TIRES [4]	9" solid or pneumatic	13" pneumatic	13" pneumatic	13" pneumatic	10" solid or pneumatic	10" pneumatic (flat-free optional) [7]	13" pneumatic (flat-free optional) [7]	10" solid (pneumatic optional) [7]	10" solid	10.75" solid
SUSPENSION	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	N/A	N/A	N/A
RANGE PER CHARGE [2,8,12]	17.8 mi / 28.6 km (tested at 200 lb / 90.7 kg)	23.4 mi / 37.7 km (tested at 220 lb / 99.8 kg)	Single Battery Option: 17.4 mi / 28 km Dual Battery Option [7]: 34.8 mi / 56 km (tested at 220 lb / 99.8 kg)	75Ah: 22.13 mi / 35.6 km 92Ah: 29.5 mi / 47.5 km (tested at 400 lb / 181 kg)	13.6 mi / 21.9 km (tested at 400 lb / 181.4 kg)	19.8 mi / 31.8 km (tested at 220 lb / 100 kg) 16.2 mi / 26 km (tested at 350 lb / 158.76 kg)	CA: 33.6 mi / 54 km HS: 22 mi / 35.4 km (tested at 350 lb / 158.7 kg)	U1: 11mi / 18 km 40Ah: S6102 -13 mi / 21 km; S7102 -13.5 mi / 21.5 km (tested at 400 lb / 181 kg)	U1: 11.1 mi / 17.8 km (tested at 350 lb / 158.7 kg)	SC901: 19.8 mi / 31.8 km SC941: 19.5 mi / 31.4 km (tested at 500 lb / 227 kg)
TOTAL WEIGHT WITHOUT BATTERIES [3,4,11]	132 lb / 60 kg	253.8 lb / 115.1 kg	220.6 lb / 100 kg	259.5 lb / 117.7 kg	165.6 lb / 75 kg	165.3 lb / 75 kg	161 lb / 73 kg	S6102: 130.25 lb / 59 kg S7102: 139 lb / 63 kg	150.5 lb / 68.3 kg	SC901: 183.5 lb / 83.3 kg SC941: 196.5 lb / 89.1 kg
WEIGHT OF HEAVIEST PIECE [4]	57 lb / 26 kg (Front Section)	201.2 lb / 91.3 kg	166 lb / 75.3 kg	205.5 lb / 93.2 kg	76.8 lb / 34.8 kg (Front Section)	68.6 lb / 31.1 kg (Front Section)	118 lb / 53.5 kg	S6102: 56.5 lb / 25.6 kg S7102: 64.5 lb / 29.2 kg (Front Section)	55 lb / 25 kg (Front Section)	SC901: 135.25 lb / 61.4 kg SC941: 143.5 lb / 65.1 kg
STANDARD SEATING [4]	Compact, Foldable (20" x 18")	High Back (19.2 x 19.5 -21.3")	High Back (20" x 18")	High Back (18" x 18")	High Back (18"x18")	High Back (18"x18")	High Back (18" x 18")	Compact, Foldable (18" x 17")	Compact, Foldable (18" x 17")	High Back (22" x 18" - 20")
BATTERY REQUIRE-MENTS	(2) U-1 [6] (SLA/AGM)	(2) 12V 75Ah [7] (SLA)	24V 50Ah [6] or Dual -24V 50Ah [7] Lithium-ion	(2) 12V 75Ah [7] or (2) 12V 100Ah [7] (SLA)	(2) 40Ah [6] (SLA/AGM)	(2) 50Ah [6] (SLA/AGM)	(2) 12V 75Ah [7] (SLA)	(2) U-1 [6] or (2) 40Ah [7] (SLA/AGM)	(2) U-1 [6] or (2) 40Ah [7] (SLA/AGM)	(2) GEL, 58Ah, NF-22 [6] (Nano-silica)
BATTERY WEIGHT [9]	25 lb / 11.3 kg [5] ea.	48.8 lb / 22.2 kg ea.	23.8 lb / 10.8 kg ea.	75Ah: 55 lb / 25 kg ea 92Ah: 60.5 lb / 27.5 kg ea	32 lb / 14.5 kg ea	31.3lb / 14.2 kg ea	53 lb / 24 kg ea.	U1: 22.5 lb 10.3 kg ea. 40Ah: 32.5 lb / 14.8 kg ea.	U1: 22.5 lb 10.3 kg ea. 40Ah: 32.5 lb / 14.8 kg ea.	36.5 lb / 16.6 kg ea.
BATTERY CHARGER	Off-board, 3.5A	Off-board, 8A	Off-board, 8A	Off-board, 8A	Off-board, 5A	Off-board, 5A	Off-board, 8A	Off-board, 3.5A	Off-board, 3.5A	Off-board, 5A
SEAT-TO-DECK HEIGHT RANGE [4]	16.5" - 18"	16.54"-18.39"	17.9"-20.9"	18"-19.5"	16.25" - 18.25"	17.25"-19.25"	17.75"-19.25"	17.5" – 18"	17.25"-18.75"	17.13" - 19.13"; or 17.36"-23.61" (with power elevating seat)
SEAT-TO-GROUND HEIGHT RANGE [4]	22"-23.5"	24.17"-25.59"	24.75"-26.75"	26.25"-27.75"	23.5" - 25.5"	23.18"-25.18"	24.75"-26.25"	23.5"- 25"	23"-24.5"	22.1" - 24.1"; or 22.32"-28.57" (with power elevating seat)

FOOTNOTES

1. Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.
2. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%.
3. Battery weight not included.
4. Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%.
5. Weight of battery and pack.
6. Batteries included.
7. Optional, up-charge may apply.
8. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed & range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or – 3 %.