

# Span F500S

Powered Sit-to-Stand Patient Lift



For users  
Requiring  
**MODERATE  
ASSISTANCE**

- **High Capacity:** 500 lb (228 kg) safe working load.
- **Care Flexibility:** Underbed clearance allows use with most low beds.
- **Safe and Reliable:** Redundant controls; overload protection; emergency lowering; 3-year frame warranty.
- **Easy operation:** Simple charging; audible/visual indicators; locking rear casters.

**SPAN**  
better science. better care.



LIFTS



SURFACES



BEDS



SEATING



FALL PROTECTION



POSITIONERS



SKIN CARE



# F500S Sit-To-Stand Patient Lift

*An essential tool for safe, efficient patient transfers between bed, chair and commode. Compact and easy to maneuver in a variety of settings, the F500S delivers a winning combination of safety, simplicity, and value.*



**LCD battery level display; audible low-battery indicator**



**2-button pendant with LED indicator**



**Underbed clearance, allows use with most low beds**



**Contoured knee pad with 3 height settings**

SPECIFICATIONS	
Weight Capacity	500 lb / 228 kg
External base width (closed)	24.9"
Internal leg width (opened)	33.9"
Upright mast height	40"
Overall base length	37.5"
Base Height	4.9"
Min. lifting height with spreader bar	38"
Max. lifting height with spreader bar	60.5"
Knee pad length extension range	4.5"
Max. boom width	17.7"
Net Weight	111 lb / 50.3 kg
Shipping Weight	119 lb / 53.9 kg

- **Easy base width adjustment** with locked position; accommodates chairs and commodes.
- **Wide non-slip footplate** provides stable base for transfer.
- **Redundant operation** via control unit, allowing use if pendant is lost or damaged.
- **Overload protection** with visual/audible alert, halts lifting when capacity is exceeded.
- **Manual emergency lowering** for added safety.
- **Quick-release battery** can be charged via charging cradle (optional), or via plug-in charger (included) for charging in place.
- **Backlit LCD display** during operation for ease of viewing.
- **Simple, fast assembly** using tools provided.
- **Certified to:** ISO 10535; IEC/EN/ANSI/AAMI/CAN/CSA-C22.2 60601-1, 60101-1-2, and 60601-1-11; SGS Mark for Safety.

Item #	Description
F500S	Sit-To-Stand Patient Lift
<b>Warranty:</b>	3 years (frame and spreader bar); 2 years (electronics); 1 year (battery)

**Part of Span's line of Safe Patient Handling and Mobility solutions, including:**

F500P Full Body Patient Lift



*Floor Lifts*

F450T Standing Transfer Aid



Fixed Lithium-ion



*Overhead Lifts*

Portable Lithium-ion

